Model 625XL3

Water Pressure Reducing Valve with Integral Strainer - Competitor Replacement Length with Venturi

TAG

Application

WILKINS model 625XL3 directly replaces a single union competitor model 25AUB and is designed for installation on potable water lines to reduce high inlet pressure to a lower outlet pressure. The integral strainer makes this device ideal for residential and commercial water systems requiring frequent cleaning because of sediment and debris. The patented integral venturi enables best-in-class flow performance, making sizing easier and providing the user ideal water pressure at higher flow rates. The integral by-pass prevents buildup of excessive system pressure caused by thermal expansion. The balanced piston design enables the pressure reducing valve to react in a smooth and responsive manner to changes in system flow demand, while at the same time, providing protection from inlet pressure changes. A removable cartridge and cost-effective repair kits significantly reduce maintenance time and costs. The valve includes premium stainless steel internals as standard to provide enhanced corrosion resistance and lasting durability.



1" 625XL3

Now tapped and plugged for 1/4" gauge (standard)

Standards Compliance

- ASSE® Listed 1003
- cUPC® Listed
- CSA® Certified B356
- Meets the requirements of NSF/ANSI/CAN 61 and 372*

*(LESS THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT)

Features

Sizes	3/4", 1", 1-1/4", 1-1/2", 2"
Maximum working water pressure	400 psi
Maximum working water temperature	140° F
Reduced pressure range	15 psi to 75 psi
Factory preset	50 psi
Threaded connections(FNPT)	ANSI B1.20.1
Copper connections (female)	ANSI B16.22

Materials

Main Valve Body	Low Lead Cast Bronze ASTM B806
Bell Housing	Low Lead Cast Bronze ASTM B806
Cartridge	NORYL™
Elastomers	EPDM (FDA approved)
	Buna Nitrile (FDA approved)
Fasteners	300 series Stainless Steel
Plunger	300 series Stainless Steel
Springs	300 series Stainless Steel
Stems	300 series Stainless Steel

Options (Suffixes can be combined)


	Standard with single union FNPT inlet x FNPT outlet
HR	High range, outlet adjust from 60 psi to 125 psi
C	Single union copper sweat x FNPT
G	Tapped and plugged with gauge

Accessories

- Repair Kits (3/4" - 2")

Suggested Pairing

- Double Check 950XL3
- Reduced Pressure Principle 975XL3



Dimensions & Weights (do not include pkg.)


SIZE		CONNECTIONS	DIMENSIONS (approximate)								WEIGHT	
			A		B		C		D			
in.	mm		in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg.
3/4	20	SINGLE UNION	5 5/16	135	4 3/4	121	1 1/2	38	1 3/4	44	1.9	0.9
1	25	SINGLE UNION	5 7/8	149	5 3/8	137	1 1/2	38	2 3/4	70	3.2	1.5
1 1/4	31	SINGLE UNION	8 1/4	210	6 1/8	156	2	51	2 3/4	70	5.3	2.4
1 1/2	38	SINGLE UNION	8 1/4	210	7 1/2	191	2 1/8	54	4 1/2	114	9.2	4.2
2	50	SINGLE UNION	8 7/8	225	7 1/2	191	2 7/16	62	4 1/2	114	10.5	4.8

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.


Flow Characteristics

Flow curves are based on a 50 psi pressure reduction. Pressure loss will be less with higher pressure reduction


3/4" MODEL 625XL3 (STANDARD AND METRIC)




1" MODEL 625XL3 (STANDARD AND METRIC)




1-1/4" MODEL 625XL3 (STANDARD AND METRIC)



1-1/2" MODEL 625XL3 (STANDARD AND METRIC)




2" MODEL 625XL3 (STANDARD AND METRIC)




Typical Installation

Local codes shall govern installation requirements. Unless otherwise specified, the assembly shall be mounted in accordance with the manufacturer's instructions and the latest edition of the Uniform Plumbing Code. The assembly shall be installed with sufficient side clearance for testing and maintenance. The Model 625XL3 may be installed in any position. Multiple installations in series are required when the desired pressure reduction is more than 3 to 1 (i.e. 150 psi inlet reduced to 50 psi outlet).

Caution: Anytime a pressure reducing valve is adjusted, a pressure gauge must be used downstream to verify correct pressure setting. Do not bottom-out adjustment bolt on bell housing.





Installation and Maintenance Instructions 3/4" Model 625XL3

Installation and Maintenance Instructions 1" - 2" Model 625XL3

Specifications

The Pressure Reducing Valve shall be certified to NSF/ANSI/CAN 61 and 372, consisting of a low lead cast bronze body, bronze bell housing, and a bolt to adjust the downstream pressure. The bronze bell housing shall be threaded to the body. The assembly shall be a balanced piston design and shall reduce pressure in both flow and no-flow conditions and maintain less than 10 psi drop from set pressure up to a flow rate of 8 ft/s. The assembly shall be accessible for maintenance without having to remove the body from the line. The assembly shall include a removable cartridge and stainless steel corrosion resistant hardware and stem. The Pressure Reducing Valve shall be a WILKINS Model 625XL3.