Hydro•X® Power Concealed Sensor Flush Valve with Exposed Back Spud for Water Closet

ZHYD40-LP

TAG _____

ARCHITECTURAL/ENGINEERING SPECIFICATION

Zurn Concealed Hydro•X® Power series of sensor flush valves for water closets are designed for reliable, hands-free operation that lasts the life expectancy of a commercial restroom. This hydropowered sensor flush valve for water closets requires no hard wiring or battery replacement, which means lower installation and maintenance costs. The gear-operated flush valve features a clog-resistant, triple filtered diaphragm. It is sensor activated to support a more hygienic environment by eliminating touch points. Pair with Hydro•X® Power faucets to maximize sustainable restroom goals.



PRODUCT FEATURES

- Architectural front access wall plate eliminates need for plumbing chase access to install & service valve, hidden fasteners for clean aesthetic and EZ access hinged opening mechanism for ease of service.
- Hydro•X® Power technology delivers sustainable performance by providing renewable, uninterrupted hydropower designed to last the life expectancy of a commercial restroom.
- Uses EZ Gear technology, a gear-driven ceramic cartridge that is less susceptbile to debris and buildup for easy maintenance; outlasts and outperforms solenoids.
- Industry-leading, triple filtered AquaVantage diaphragm, gaskets and seals are made of chemical-resistant thermoplastic elastomer, which lasts 8-10 times longer than traditional rubber, reducing maintenance costs.
- Automatic touchless sensor activation reduces guest visits without a flush and can help reduce germ transmission.
- Electronic override button delivers on-demand manual flushing.
- Heavy-duty wall plate construction with a highly polished chrome-plated, brushed nickel or matte black PVD finishes provides long-term durability and vandal resistance in a contemporary design.
- Standard 24-hour line flushing to help minimize stagnation and maintain fixture trap seals to protect against sewer gases during periods of inactivity.
- User-in-view LED indicator light.
- Concealed flush valve is furnished with a high-pressure vacuum breaker tube assembly, 1" wheel control stop with internal siphon-guard protection, sweat solder kit for 1-1/2" exposed back spud inlet
- Wall plate dimensions: 11" (W) x 12.5" (H)
  Wall Opening: 10" (W)x 11 ½" (H)
- Operating Pressure
  25 psi (running) - 80 psi (static)
  Higher running pressure may be required for some fixtures
  Consult fixture manufacturer for details

COMPLIANCE AND CERTIFICATION

- Complies with ASSE 1037/ASME A112.1037/CSA B125.37
- ADA Compliant

*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE* CEC, & CALGREEN COMPLIANT
☐ **-ONE**	1.1	✓
☐ **-HET**	1.28	✓
☐ **-WS1**	1.6	
☐ **-HET-DF**	1.28/1.1	✓
☐ **-WS1-DF**	1.6/1.1	

ALTERNATIVE FINISHES

☐ -BN Brushed Nickel
☐ -MB Matte Black

WHEN INSTALLING IN A HANDICAP STALL:


Per the ADA Guidelines (section 604.9.4) it is recommended that the grab bars be split or shifted to the wide side of the stall. If grab bars must be present over the valve, use the alternate ADA installation as shown.

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.

Rev. B | Date: 11/11/2026 | C.N. No. 148426 | Prod./Dwg. No. SS ZHYD40-LP

Rough-in dimensions/Overview dimensions



ALTERNATE ADA INSTALLATION

Lower water supply rough-in to 10” and mount grab bar at the 36” maximum allowed height.