



ARCHITECTURAL & ENGINEERING SPECIFICATION

Complete manual hand washing system includes 20" [508mm] x 18" [457mm] vitreous china wall hung lavatory with Z812B1-XL-3F, polished chrome-plated 5-3/8" [137mm] gooseneck faucet with lever handles and a 0.5 gpm aerator, Z8743-PC chrome-plated cast brass solid top grid strainer, Z8700-8B-PC series P-trap, and Z8804-XL-LRLK-PC series supply stop kit manufactured by Zurn.

PRODUCT FEATURES

- 20" [508 mm] x 18" [457 mm] vitreous china lavatory
- Wall hung lavatory provided with wall hanger bracket
- Front overflow
- Waste: 1-1/4" O.D.
- Depth: 5-3/4"
- Quarter turn ceramic disc faucet operation
- Chrome-plated cast brass faucet body
- 2-1/2" vandal-resistant color-coded metal lever handles
- 5-3/8" [137mm] centerline rigid or swing gooseneck spout
- Chrome-plated cast brass open grid drain strainer
- Chrome-plated cast body, p-trap less clean-out
- Chrome-plated, solid brass angle stops with loose key

COMPLIANCE AND CERTIFICATION:

Meets the American Disabilities Guidelines and ANSI A117.1 requirements when installed according to these requirements.

- Fixture - Complies with ASME A112.19.2 / CSA B45.1
- Faucet - Complies with ASME A112.18.1 / CSA B125.1



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



ZURN ONE SYSTEM PACKOUT INCLUDES:

LAVATORY - Z5344:

20" [508mm] x 18" [457mm] vitreous china wall hung lavatory with 4" [101mm] center faucet holes. Provided with hanger plate and holes for concealed arm carrier system

FAUCET - Z812B1-XL-3F:

Polished chrome-plated cast brass faucet body with integral shanks, quarter turn ceramic disc cartridges and a 5-3/8" [137mm] centerline rigid or swing gooseneck spout with a 0.5 gpm vandal-resistant pressure compensation aerator

Z8743-PC:

Chrome-plated cast brass solid top, open grid, P.O. plug. Furnished with 5" [127mm] long, chrome-plated brass 17 gauge tailpiece and chrome-plated cast brass locknut

Z8700-8B-PC:

Chrome-plated, cast body P-trap less clean-out, tubular wall bend, die cast nuts, and shallow escutcheon with compression inlet

Z8804-XL-LRLK-PC:

Two chrome-plated, solid brass angle stops with 1/2" [13mm] NOM compression inlet, 3/8" [10mm] OD compression outlet, loose key, two 12" [305mm] flexible chrome-plated copper lavatory risers complete with two chrome-plated steel flanges and 5" [127mm] chrome-plated copper extension tubes, deep bell steel flanges



The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions

