

## ARCHITECTURAL & ENGINEERING SPECIFICATION

Complete sensor hand washing system includes 20"x18" vitreous china wall hung lavatory with ZG6915-XL-TMV-1, ADA compliant, hydropowered, chrome plated 4" wide base sensor faucet with thermostatic mixing valve, Z8746-PC chrome plated cast brass solid offset top grid strainer, Z8700B-PC series P-trap, Z8946-3-NT protector combination kit, and Z8804-XL-LK-PC series supply stop kit.

## PRODUCT FEATURES

- 20" [508 mm] x 18" [457 mm] vitreous china lavatory
- Wall hung lavatory provided with wall hanger bracket or for use with concealed arm carrier systems
- Front overflow
- Infrared convergence-type proximity sensor
- 30 second time out feature
- Shipping weight: 60lbs
- Chrome-plated faucet cast brass body
- Thermostatic mixing valve to help prevent scalding
- Complete commercial grade grid drain, P-Trap, supply

## COMPLIANCE AND CERTIFICATION:

Meets the American Disabilities Guidelines and ANSI A117.1 requirements when installed according to these requirements.

- Fixture - Complies with ASME A119.2 / CSA B45.1
- Faucet - Complies with ASME A112.18.1 / CSA B125.1



## ZURN ONE SYSTEM PACKOUT INCLUDES:

### FIXTURE - Z5344:

20" x 18" vitreous china wall hung lavatory with 4" [102mm] center faucet holes. Provided with hanger plate and holes for concealed arm carrier systems.

### FAUCET - ZG6915-XL-TMV-1:

ADA compliant, hydropowered, chrome plated 4" wide base sensor faucet with point of use thermostatic mixing valve to prevent scalding and a 0.5 gpm vandal-resistant nonaerated outlet.

### Z8746-PC:

Chrome plated cast brass open grid drain strainer, and chrome plated cast brass elbow. Furnished with 1-1/4[32] 17 gauge, chrome plated tubular brass offset tailpiece for sink depth to 2-1/2[57].

### Z8700B-PC:

Chrome-plated cast brass (copper alloy) body p-trap

### Z8946-3-NT:

Combination Kit: One trap protector, two supply stop protectors and one offset drain protector, satin white PVC resin, ZurnSHIELDTM, resists thermal transfer and is ADA compliant. Trap protector fits both tubular and semi-cast P traps.

### Z8804-XL-LK-PC:

Zurn chrome-plated, solid brass angle stop compression to compression fitting with loose key and risers.

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in / Overview dimensions

