

Architectural/Engineering Specification:

Polished chrome-plated cast brass faucet body with integral shanks, quarter turn ceramic disc cartridges and a 5-3/8" rigid or swing spout. Unit is furnished with a standard 2.2 GPM aerator, vandal-resistant color-coded handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

PRODUCT FEATURES:

- Ceramic Disc Cartridge
- Chrome-plated Cast Brass Body
- 2" Vandal Resistant Color Coded Dome Lever Handles

SUFFIX OPTIONS:

	out the or fronts.						
		-140	140 degree Restricted Swing Gooseneck Spout				
-G 1-1/		-G	1-1/4" [32mm] Grid Strainer Drain				
		-P	1-1/4" [32mm] Pop-up Drain				

AERATOR OPTIONS:

ALKATOR OPTIONS.									
	Suffix	Flowrate GPM [L]	Vandal-Resistant	WaterSense* Labeled	Pressure Compensating	Outlet Type			
	-17F	1.5 GPM [5.7L]	Х	Х	Х	Aerator			
	-18F	1.5 GPM [5.7L]	Х	Х	Х	Laminar			
	-FC1.5	1.5 GPM [5.7L]		Х	Х				
	-FC1.0	1.0 GPM [3.8L]		Х	X				
	-7F	1.0 GPM [3.8L]		Х	Х	Spray			
	-16F	1.0 GPM [3.8L]	Χ		Х	Spray			
	-22F	1.0 GPM [3.8L]	Х			Laminar			
	-25F	0.35 GPM [1.3L]	Χ		Х	Spray			
	-28F	0.5 GPM [1.9L]	Х			Laminar			
	-2F	2.2 GPM [8.3L]	Х			Aerator			
	-3F	0.5 GPM [1.9L]	Х			Spray			
	-4F	2.2 GPM [8.3L]	Х			Laminar			
	-FC	2.0 GPM [7.6L]			Х				
	-FC0.5	0.5 GPM [1.9L]			Х				
	-27F	0.5 GPM [1.9L]				Laminar			



Product Compliance:

ASME A112.18.1/CSA B125.1 IPC NSF 61

*Although products with certain combinations of options and features will meet or comply with these standards and/or certifications, not every combination of options and features will result in such compliance. If you have any questions about your particular product, please contact our Customer Care Dept. at 1-855-ONE-ZURN (United States) or 1-877-892-5216 (Canada) for confirmation.

NSF 372

Installation Guide - CF1170.pdf


Architectural/Engineering Approval

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

▲ WARNING: Cancer and Reproductive Harm – <u>www.P65warnings.ca.gov</u>

▲ ADVERTENCIA: Cáncer y daño reproductivo – <u>www.P65warnings.ca.gov</u>





NOTE: All dimensions are for reference only. Do not use for pre-plumbing.

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

▲ WARNING: Cancer and Reproductive Harm – <u>www.P65warnings.ca.gov</u>

ADVERTENCIA: Cáncer y daño reproductivo – <u>www.P65warnings.ca.gov</u>

AVERTISSEMENT: Cancer et effets néfastes sur la reproduction – <u>www.P65warnings.ca.gov</u>