



Model(s) Z825F1-XL

Single Laboratory Faucet 6" Cast Iron Spout with 2-1/2" Lever Handle (Lead Free)

TAG

Architectural/Engineering Specification:

Polished chrome-plated single laboratory faucet with integral shank, a quarter turn ceramic disc cartridge and a 6" [152mm] cast brass swing spout. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), a 2-1/2" [64mm] vandal-resistant color-coded metal lever handle, mounting hardware and a 1/2" NPSM coupling nut for standard lavatory riser.

Zurn Lead Compliant* "XL" products are a line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn "XL" products are manufactured with *not more than 0.25% lead content when used with respect to wetted surfaces of pipes and pipe fittings, plumbing fitting and fixtures: California Health & Safety Code § 116875; Vermont 9 VCA § 2470h.



SUFFIX OPTIONS:

-AR	Anti-Rotation Pins
-G	1-1/4" [32mm] Grid Strainer Drain

AERATOR OPTIONS:

	Suffix	Flowrate GPM [L]	Vandal-Resistant	Pressure Compensating	Outlet Type
	-16F	1.0 GPM [3.8L]	x	x	Spray
	-17F	1.5 GPM [5.7L]	x	x	Aerator
	-18F	1.5 GPM [5.7L]	x	x	Laminar
	-22F	1.0 GPM [3.8L]	x		Laminar
	-25F	0.35 GPM [1.3L]	x	x	Spray
	-26F	0.5 GPM [1.9L]			Spray
	-28F	0.5 GPM [1.9L]	x		Laminar
	-2F	2.2 GPM [8.3L]	x		Aerator
	-3F	0.5 GPM [1.9L]	x		Spray
	-4F	2.2 GPM [8.3L]	x		Laminar
	-7F	1.0 GPM [3.8L]		x	Spray
	-27F	0.5 GPM [1.9L]			Laminar

Product Compliance:

ADA
ASME A112.18.1/CSA B125.1
CSA B125.1

*Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

**Although products with certain combinations of options and features will meet or comply with these standards and/or certifications, not every combination of options and features will result in such compliance. If you have any questions about your particular product, please contact our Customer Care Dept. at 1-855-ONE-ZURN (United States) or 1-877-892-5216 (Canada) for confirmation.*

[Installation Guide - CF1531.pdf](#)

Architectural/Engineering Approval

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

⚠ WARNING: Cancer and Reproductive Harm – www.P65warnings.ca.gov

⚠ ADVERTENCIA: Cáncer y daño reproductivo – www.P65warnings.ca.gov

⚠ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction – www.P65warnings.ca.gov

by Zurn Elkay Water Solutions

ZURN.COM

Patent zurn.com/patents

© 2025 Page 1

5900 Elwin Buchanan Drive, Sanford, NC 27330
US 1.855.ONE.ZURN Sensor.Products@zurn.com
3544 Nashua Drive, Mississauga, Ontario L4V1L2
CANADA 1.877.892.5216 Sensor.Products@zurn.com


[Z825F1-XL](#)
[Z825F1-XL_spec.pdf](#)
REV 9/11/2025



Model(s) Z825F1-XL

Single Laboratory Faucet 6" Cast Iron Spout with 2-1/2" Lever Handle (Lead Free)

TAG



NOTE: All dimensions are for reference only. Do not use for pre-plumbing.

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

⚠ WARNING: Cancer and Reproductive Harm – www.P65warnings.ca.gov

⚠ ADVERTENCIA: Cáncer y daño reproductivo – www.P65warnings.ca.gov

⚠ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction – www.P65warnings.ca.gov