



Model(s) Z831C4-XL

Widespread, Gooseneck Faucet

TAG _____

Architectural/Engineering Specification:

Polished chrome-plated widespread with adjustable centers from 6" to 20", an 8" rigid or swing spout and quarter turn ceramic disc cartridges. Unit is furnished with a standard 2.2 GPM aerator, vandal-resistant color-coded handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. Widespread accommodates installations up to 1-1/8" thick. Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

PRODUCT FEATURES:

- Ceramic Disc Cartridge
- Chrome-plated Cast Brass Body
- Widespread Handles Adjustable From 6" to 20" Centers
- 4" Vandal Resistant Color Coded Wrist Blade Handles

AERATOR OPTIONS:

	Suffix	Flowrate GPM [L]	Vandal-Resistant	WaterSense* Labeled	Pressure Compensating	Outlet Type
	-FC1.0	1.0 GPM [3.8L]		x	x	
	-7F	1.0 GPM [3.8L]		x	x	Spray
	-18F	1.5 GPM [5.7L]	x	x	x	Laminar
	-17F	1.5 GPM [5.7L]	x	x	x	Aerator
	-FC1.5	1.5 GPM [5.7L]		x	x	
	-16F	1.0 GPM [3.8L]	x		x	Spray
	-22F	1.0 GPM [3.8L]	x			Laminar
	-25F	0.35 GPM [1.3L]	x		x	Spray
	-26F	0.5 GPM [1.9L]				Spray
	-28F	0.5 GPM [1.9L]	x			Laminar
	-2F	2.2 GPM [8.3L]	x			Aerator
	-3F	0.5 GPM [1.9L]	x			Spray
	-4F	2.2 GPM [8.3L]	x			Laminar
	-FC	2.0 GPM [7.6L]			x	
	-FC0.5	0.5 GPM [1.9L]			x	
	-27F	0.5 GPM [1.9L]				Laminar



Product Compliance:

ADA
ASME A112.18.1/CSA B125.1
CEC
CSA B125.1
IPC
NSF 61
NSF 372

*Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

**Although products with certain combinations of options and features will meet or comply with these standards and/or certifications, not every combination of options and features will result in such compliance. If you have any questions about your particular product, please contact our Customer Care Dept. at 1-855-ONE-ZURN (United States) or 1-877-892-5216 (Canada) for confirmation.*

[Installation Guide - CF1197.pdf](#)


Architectural/Engineering Approval

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

⚠ WARNING: Cancer and Reproductive Harm – www.P65warnings.ca.gov

⚠ ADVERTENCIA: Cáncer y daño reproductivo – www.P65warnings.ca.gov

⚠ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction – www.P65warnings.ca.gov



Technical drawing of a three-way gas valve assembly. The drawing includes the following dimensions and labels:

- $\phi 2[51]$: Dimension for the vertical pipe section.
- $\phi 1\frac{1}{8}[29]$: Dimension for the horizontal pipe section.
- MIN. WARE: Label for the minimum working distance.
- 4 [103]: Dimension for the horizontal distance between the two side valves.
- $4\frac{1}{4}[108]$: Dimension for the vertical distance from the base to the top of the side valves.
- $\phi 2\frac{1}{4}[57]$: Dimension for the horizontal distance between the two side valves.
- $\phi 1\frac{1}{4}[32]$: Dimension for the horizontal distance between the two side valves.
- $4\frac{1}{4}[108]$: Dimension for the vertical distance from the base to the top of the side valves.
- $\frac{1}{2}$ TO $1\frac{1}{8}[29]$: Dimension for the horizontal distance between the two side valves.
- WARE: Label for the working distance.
- $\frac{1}{2}$ -14 NPSM COUPLING NUT: Label for the coupling nut.
- 8[203]: Dimension for the horizontal distance between the two side valves.
- $6\frac{7}{8}[175]$: Dimension for the vertical distance from the base to the top of the side valves.
- 8[203]: Dimension for the horizontal distance between the two side valves.
- $12\frac{1}{2}[318]$: Dimension for the vertical distance from the base to the top of the side valves.

[Z831C4-XL](#)
[Z831C4-XL spec.pdf](#)
REV 9/11/2025