



# Model(s) Z831R1-XL

Widespread Faucet with 5" cast spout and lever handles

TAG \_\_\_\_\_

### Architectural/Engineering Specification:

Polished chrome-plated widespread with adjustable centers from 6" [152mm] to 20" [508mm], a 5" [127mm] centerline cast brass low profile spout and quarter turn ceramic disc cartridges. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 2-1/2" [64mm] vandal-resistant colorcoded metal lever handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. Widespread accommodates installations up to 1-1/8" [29mm] thick.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

### PRODUCT FEATURES:

- Ceramic Disc Cartridge
- Chrome-plated Cast Brass Body
- 2-1/2" Vandal Resistant color coded metal lever handles

### SUFFIX OPTIONS:

<input type="checkbox"/>	-G	1-1/4" [32mm] Grid Strainer Drain
<input type="checkbox"/>	-ICT	Inter-connecting Copper Supply Tubes for 8" In-line Centers
<input type="checkbox"/>	-P	1-1/4" [32mm] Pop-up Drain

### AERATOR OPTIONS:

	Suffix	Flowrate GPM [L]	Vandal- Resistant	Pressure Compensating	Outlet Type
<input type="checkbox"/>	-16M	1.0 GPM [3.8L]	x	x	Spray
<input type="checkbox"/>	-17M	1.5 GPM [5.7L]	x	x	Aerator
<input type="checkbox"/>	-18M	1.5 GPM [5.7L]	x	x	Laminar
<input type="checkbox"/>	-22M	1.0 GPM [3.8L]	x		Laminar
<input type="checkbox"/>	-25M	0.35 GPM [1.3L]	x	x	Spray
<input type="checkbox"/>	-27M	0.5 GPM [1.9L]			Laminar
<input type="checkbox"/>	-28M	0.5 GPM [1.9L]	x		Laminar
<input type="checkbox"/>	-2M	2.2 GPM [8.3L]	x		Aerator
<input type="checkbox"/>	-3M	0.5 GPM [1.9L]	x		Spray
<input type="checkbox"/>	-4M	2.2 GPM [8.3L]	x		Laminar
<input type="checkbox"/>	-7M	1.0 GPM [3.8L]		x	Spray



### Product Compliance:

- ADA
- ASME A112.18.1/CSA B125.1
- CEC
- CSA B125.1
- IPC
- NSF 61
- NSF 372

\*Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.


*\*Although products with certain combinations of options and features will meet or comply with these standards and/or certifications, not every combination of options and features will result in such compliance. If you have any questions about your particular product, please contact our Customer Care Dept. at 1-855-ONE-ZURN (United States) or 1-877-892-5216 (Canada) for confirmation.*

[Installation Guide - CF1197.pdf](#)

Architectural/Engineering Approval

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

⚠ WARNING: Cancer and Reproductive Harm – [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)  
 ⚠ ADVERTENCIA: Cáncer y daño reproductivo – [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)  
 ⚠ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction – [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)



NOTE: All dimensions are for reference only. Do not use for pre-plumbing.

Design and dimensional data (inches and [mm]) are subject to manufacturing tolerances and change without notice.

⚠ WARNING: Cancer and Reproductive Harm - [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

⚠ ADVERTENCIA: Cáncer y daño reproductivo - [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

⚠ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction - [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)